

HOT SHOT SERIES

GAS, DIRECT DRIVE



4012-10A

4GPM@4000PSI



RRV4G40D-F24 Pump

POWERED by

HONDA™ GX390 Engine

Standard Accessories

- ◆ Gun/wand assembly with insulated grip and quick connects
- ◆ 50' high pressure hose w/quick connects
- ◆ Maxi-Flo 20% chemical injector assembly w/quick connects
- ◆ 4 color-coded QC spray nozzles
- ◆ 1 color-coded QC chemical nozzle

Standard Options

- ◆ ATK005 Adjustable Thermostat
- ◆ BRK100 Brake Kit
- ◆ HRK415 Hose Reel Kit, 150' x 3/8" max. w/ no add'l hose
- ◆ MC-B135 Machine Cover Blue Poly Marine Fabric

NOTE: AR, CAT, and VIPER gear drive pumps available – consult factory.

Standard Features

- ◆ Rugged powder coated steel roll cage frame w/ lifting hook & 13" flat-free tires & threaded axles
- ◆ 4-wheel dimensions: 39" L x 31" W x 49" H
- ◆ Super efficient schedule 80 coil w/ one-piece molded insulation combustion chamber
- ◆ Stainless steel coil wrap
- ◆ 8 gallon poly diesel fuel tank w/ fuel filter
- ◆ Commercial/Industrial grade engines
- ◆ Reliable Beckett burners
- ◆ High limit over temp protection
- ◆ Safety pressure relief valve
- ◆ Thermo-sensor (prevents over heating in bypass mode)

NOTE: Gasoline Honda and Diesel powered models include electric start, and battery w/ marine battery box.

Pressure-Pro®